



차량 충격 테스트

H사 SUV차량을 이용한 일반 도로 위 제품 상단방향 차량 주행 충격 진행
<영상 : 유튜브 HANIS CS 채널>



IP65급
방진방수 기능



작업환경 맞춤
다각도 스캐닝



장시간 작업
대용량 배터리



SM2

1500MAH 대용량 배터리 탑재와 QR코드 등 다양한 2D바코드 완벽 스캔
국내생산으로 더 믿을 수 있는 품질 제공

 대한통운 공식 지정 장비로 운영중

HANIS

본사 경기도 광명시 소하로 190 광명G타워 518~520호
판매/기술지원 TEL. 070-8648-1924
HANIS는 주식회사 바인의 ICT브랜드입니다.
© 2022. HANIS all rights reserved.
www.hanis.co.kr



HANIS
MALL

제품 사양

SOFTWARE SUPPORT

Keyboard Pro
SDK Demo
OTA Tools
iCode
My Hanis



HANIS

본사 경기도 광명시 소하로 190 광명G타워 518~520호

판매/기술지원 TEL. 070-8648-1924

HANIS는 주식회사 바인의 ICT 브랜드입니다.

© 2022. HANIS all rights reserved.

www.hanis.co.kr

특성 PHYSICAL CHARACTERISTICS

크기	82mm(L)×46mm(W)×20mm(D) 3.22in.(L)×1.81in.(W)×0.79in.(D) 표준 배터리 포함 : 68g /2.4oz
무게	5V = 1A 1500mAh
배터리 용량	100min
충전	32h (매 5초 간격 트리거 기준)
충전 시간	LED, 바저, 진동 사용 가능.
작업 시간	
알림	

DECODE RANGES

5MIL CODE39	5.1cm~16.2cm/2.0in.~6.4in.
5MIL CODE128	6.3cm~12.7cm/2.5in.~5.0in.
6.6MIL PDF417	6.3cm~16.0cm/2.5in.~6.3in.
10MIL PDF417	4.5cm~22.8cm/1.8in.*~9.0in.
13MIL 100% UPC	5.0cm*~31.7cm/2.0in.*~12.5in.
20MIL CODE39	5.0cm*~49.5cm/2.0in.*~19.5in.
20MIL DATAMATRIX	3.8cm~34.3cm/1.5in.~13.5in.
20MIL QR CODE	3.8cm~27.9cm/1.5in.~11.0in.

블루투스 BLUETOOTH

개요	HID Keyboard, SPP and Bluetooth low energy (BLE)
범위	Communication distance connected to mobile phone > 164.04ft./50m (without obstructions)
OTA	HID Keyboard, SPP and Bluetooth low energy (BLE)
USB	
USB INTERFACE	USB Type-C
USB PROFILES	USB HID Keyboard, USB VCP (Virtual Serial Port)
MULTILINGUAL KEYBOARDS	USB HID mode supports multilingual keyboards

사용자 환경 USER ENVIRONMENT

주변광	Max 107,639 lux (direct sunlight)
보관/작동 온도	14°F ~ 122°F / -10°C~50°C
습도	5% to 85% non-condensing
DROP SPEC	Multiple 4.9 ft./1.5 m drops to concrete over the operating temperature range.
TUMBLE SPEC	Scanner body withstands 20,000 3.3ft./1.0 m tumbles.
ELECTROSTATIC DISCHARGE (ESD) CERTIFICATION	±8kVdc contact discharge; ±15kVdc air discharge CE, KC, RoHS

성능 특성 PERFORMANCE CHARACTERISTICS

광학 해상도	640 x 400 pixels
센서	2D CMOS Image
SKREW, PITCH & ROLL	Skew tolerance : ±60° Pitch tolerance : ±60° Roll tolerance : 360°
시야	42° horizontal, 28° vertical
조명 요소	1 Hyper Red 660nm LED
조준 요소	610nm LED
SUPPORTED SYMBOLOGIES	UPC-A, UPC-E, UPC-ET, EAN-8 JAN 8, EAN-13/-JAN 13, Bookland EAN, ISSN EAN, Code 128, GS1-128, ISBT-128, Code 39, Trioptic Code 39, Code 93, Code 11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Matrix 2 of 5, Codabar, MSI, GS1 Databar-14, GS1 Databar Limited, GS1 Databar Expanded, Composite Codes : Composite CC-C, Composite CC-A/B, Compo PDF417, MicroPDF417, Code 128 Emulation, DataMatrix, Maxicode, QR Code, MicroQR Code Aztec Code, Han Xin
INTERFACE	USB, Bluetooth
OFFLINE MODE	Support storage 5000 EAN-13 barcodes

ETC

제조

대한민국



070-8648-1923~4

cs@hanis.co.kr